## Li-Wall series


# **Lithium Iron Phosphate Battery**


### Overview

The VOLTAI- 25.6V200Ah rechargeable lithium battery is optimized for low rate application which reqiures high energy density.

#### **Features**

- LiFePO4 battery, more stable and safe.
- Intelligent BMS equipped inside to maintain the battery always work at best condition.
- Max. charge and discharge current as 200A which is specially designed for solar energy.
- With equalizer can balance each lithium cell voltage difference as small as 0.05V in a very short time.
- Excellent standby self-consumption as low as 4mA.
- Within VOLTAI solar inverter Modbus-485 communication protocol.
- Automatically output cut off after 30days no charge and discharge to ensure security, also can cut off output by manual operation .





## **Battery Specification**

Nominal Voltage ∕V	25.6
Nominal Capacity /Ah (25° C , 0.2C)	200
Mechanical characteristics	
Weight (approximate)/Kg	57.0
Dimension L*W*H /mm	550*375*227
Terminal	M8
Electrical characteristics	
Voltage window/V	22.4 to 29.2
Float charge voltage/V	28.0
Max. continue discharge current/A	100
Max. pulse discharge current/A	200A 30Sec.
Max. continue charge current/A	100
Operating conditions	
Cycle life (+25℃ 0.2C 100%DOD)	> 3000 Cycles
Operating temperature	Discharge -10°C to 50°C Charge 0°C to 50°C
Storage temperature	0 to 30℃
Storage duration	6 months at 25°C
Safety standard	UN38.3,MSDS
IP Degree	IP20
Dis charge curves under differnet tempertatures	Cycle life vervus DOD and temperture at 0.2
- 60°, b 2c 28°, p 2c 16°, b 2c	5000 5000 4000 4000 5000 5000 5000 6000 5000 6000
0.2C CC-CV charge charavteristic	Self-discharge characteristic
0.3 O O O O O O O O O O O O O O O O O O O	110 100 (%) 40 (%) 40 (



